

Removing Current Pump Graphics

1. **Choose the right day**

The temperature to be at least 45 degrees Fahrenheit, though 60 degrees or warmer is preferred for both removal and installation. Humidity above 90% can negatively affect decal install.

2. **Peel off the old graphic**

Wedge a plastic squeegee or card between the decal and the pump surface using a consistent, slight pressure and a back-and-forth motion. When enough of the graphic has been peeled away, grab onto it and tug the remainder of the graphic off.

3. **Scrape off any remaining bits of decal**

If needed, use a quality scraping razor the same way you used the squeegee to remove any stubborn bits of decal. A rag and hot water can be used to heat the decal and make the adhesive easier to remove.

NEVER use a heat gun, blow dryer, or other electric tools to remove pump decals, as they can cause an explosion.

4. **Remove the remaining adhesive residue**

Some residue can be removed with a soapy cloth and squeegee while some material, especially polycarbonate overlays, may require an adhesive removing agent such as rubbing alcohol, acetone, Goo Gone, or Rapid Remover.

Please note that removing agents may damage other parts of the pump. Some installation professionals recommend using a thin layer of peanut butter on adhesive residue overnight as the high fat content effectively dissolves adhesive.

5. **Give the area a final wash**

Wipe the adhesive-free surface with a damp cloth, and dry the area, removing any excess residue or dirt. For the best results, use a petroleum-based or automotive-grade cleaner and wax remover.

Installing New Pump Graphics

1. **Prepare the surface**

After your surface has been cleaned and dried, wipe it with 70% or higher isopropyl alcohol using a lint-free cloth.

2. **Position the graphic**

Remove the entire backing of the graphic, and tack the decal in position with minimal thumb pressure in the upper corners only. Many dispensers have raised edges to indicate where the decal should go.

3. **Adhere the graphic**

Using a plastic squeegee and firm pressure, start at the center of the decal and slide the squeegee outward to the edges in each direction, removing wrinkles and air pockets. Run the squeegee around all four edges with very firm pressure to ensure a complete seal.

If vinyl graphics have any air bubbles, poke a hole in the bubble with a pin, and smooth the decal out with your finger or a squeegee.